

## CLAIMS

1. A semiconductor device comprising:  
a transistor;  
5 a current supply means electrically connected to the transistor; and  
a precharge circuit comprising a first terminal electrically connected to the  
transistor and a second terminal;  
wherein the precharge circuit supplies a charge to the transistor according to a  
comparison between a potential of the first terminal and a potential of the second  
10 terminal.
2. A semiconductor device according to Claim 1, wherein the precharge circuit  
comprising:  
a comparison control circuit for the comparison between the potential of the first  
15 wiring and the potential of the second wiring; and  
a switch controlled by the comparison control circuit;
3. A semiconductor device according to Claim 2, wherein the comparison  
control circuit comprises an operational amplifier.  
20
4. A semiconductor device according to Claim 2, wherein the comparison  
control circuit comprises a chopper inverter transistor.
5. An electronic apparatus having the semiconductor device according to Claim  
25 1, wherein the electronic apparatus is selected from the group consisting of a light  
emitting device, a digital still camera, laptop personal computer, a mobile computer, a  
portable image reproducing device, a goggle type display, a video camera and a portable  
phone.
- 30 6. A semiconductor device comprising:

a transistor;  
a current source electrically connected to the transistor;  
a charge supply means; and  
a precharge circuit comprising:

5                   a comparison control circuit having a first terminal electrically connected  
to the transistor, a second terminal and third terminal; and

                  a switch electrically connected the third terminal;  
wherein the charge supply means is electrically connected to the transistor.

10               7. A semiconductor device according to Claim 6, wherein the charge supply  
means is a current source.

                  8. A semiconductor device according to Claim 6, wherein the charge supply  
means is a power source.

15               9. The semiconductor device according to Claim 6, wherein the comparison  
control circuit comprises an operational amplifier.

                  10. The semiconductor device according to Claim 6, wherein the comparison  
20 control circuit comprises a chopper inverter transistor.

                  11. An electronic apparatus having the semiconductor device according to Claim  
6, wherein the electronic apparatus is selected from the group consisting of a light  
emitting device, a digital still camera, laptop personal computer, a mobile computer, a  
25 portable image reproducing device, a goggle type display, a video camera and a portable  
phone.

                  12. A semiconductor device comprising:  
a transistor comprising a source electrode, a drain electrode and a gate electrode;  
30 a current source electrically connected to the transistor;

a charge supply means; and

a precharge circuit comprising:

a comparison control circuit having a first terminal electrically connected to the transistor, a second terminal and third terminal; and

5 a switch electrically connected the third terminal;

wherein the gate electrode is electrically connected to any one of the source electrode and the drain electrode, and

wherein the charge supply means is electrically connected to any one of the source electrode and the drain electrode.

10

13. A semiconductor device according to Claim 12, wherein the charge supply means is a current source.

14. A semiconductor device according to Claim 12, wherein the charge supply  
15 means is a power source.

15. The semiconductor device according to Claim 12, wherein the comparison control circuit comprises an operational amplifier.

20 16. The semiconductor device according to Claim 12, wherein the comparison control circuit comprises a chopper inverter transistor.

17. An electronic apparatus having the semiconductor device according to Claim 12, wherein the electronic apparatus is selected from the group consisting of a light  
25 emitting device, a digital still camera, laptop personal computer, a mobile computer, a portable image reproducing device, a goggle type display, a video camera and a portable phone.

18. A display device comprising:  
30 a pixel;

a transistor;

a current supply means electrically connected to the transistor; and

a precharge circuit comprising a first terminal electrically connected to the transistor and a second terminal;

5        wherein the precharge circuit supplies a charge to the transistor according to a comparison between a potential of the first terminal and a potential of the second terminal, and

       wherein the transistor supplies a current to the pixel.

10       19. A display device according to Claim 18,  
       wherein the pixel has a light emitting element, and  
       wherein the transistor supplies a current to the light emitting element.

       20. A display device according to Claim 18, wherein the precharge circuit  
15    comprising:  
       a comparison control circuit for the comparison between the potential of the first wiring and the potential of the second wiring; and  
       a switch controlled by the comparison control circuit;

20       21. A display device according to Claim 20, wherein the comparison control circuit comprises an operational amplifier.

       22. A display device according to Claim 20, wherein the comparison control circuit comprises a chopper inverter transistor.

25       23. An electronic apparatus having the display device according to Claim 18,  
       wherein the electronic apparatus is selected from the group consisting of a light emitting device, a digital still camera, laptop personal computer, a mobile computer, a portable image-reproducing device, a goggle type display, a video camera and a portable phone.

24. A display device comprising:

a pixel;

a transistor electrically connected to the pixel;

a current source electrically connected to the transistor;

5 a charge supply means; and

a precharge circuit comprising:

a comparison control circuit having a first terminal electrically connected to the transistor, a second terminal and third terminal; and

a switch electrically connected the third terminal;

10 wherein the charge supply means is electrically connected to the transistor.

25. A display device according to Claim 24,

wherein the pixel has a light emitting element, and

wherein the transistor is electrically connected to the light emitting element.

15

26. A display device according to Claim 24, wherein the charge supply means is a current source.

27. A display device according to Claim 24, wherein the charge supply means is  
20 a power source.

28. The display device according to Claim 24, wherein the comparison control circuit comprises an operational amplifier.

25 29. The display device according to Claim 24, wherein the comparison control circuit comprises a chopper inverter transistor.

30. An electronic apparatus having the display device according to Claim 24, wherein the electronic apparatus is selected from the group consisting of a light emitting  
30 device, a digital still camera, laptop personal computer, a mobile computer, a portable

image reproducing device, a goggle type display, a video camera and a portable phone.

31. A display device comprising:

a pixel;

5 a transistor comprising a source electrode, a drain electrode and a gate electrode;

a current source electrically connected to the transistor;

a charge supply means; and

a precharge circuit comprising:

10 a comparison control circuit having a first terminal electrically connected to the transistor, a second terminal and third terminal; and

a switch electrically connected the third terminal;

wherein the gate electrode is electrically connected to any one of the source electrode and the drain electrode,

15 wherein the charge supply means is electrically connected to any one of the source electrode and the drain electrode, and

wherein the pixel is electrically connected to any one of the source electrode and the drain electrode.

20 32. A display device according to Claim 31, wherein the charge supply means is a current source.

33. A display device according to Claim 31, wherein the charge supply means is a power source.

25 34. The display device according to Claim 31, wherein the comparison control circuit comprises an operational amplifier.

35. The display device according to Claim 31, wherein the comparison control circuit comprises a chopper inverter transistor.

36. An electronic apparatus having the display device according to Claim 31, wherein the electronic apparatus is selected from the group consisting of a light emitting device, a digital still camera, laptop personal computer, a mobile computer, a portable image reproducing device, a goggle type display, a video camera and a portable phone.